

AdiIRC - \$ial - # 10

Added in 1.9.0

\$ial

Returns [\\$true](#) if Internal Address List is enabled, otherwise [\\$false](#).

Always returns [\\$true](#) in AdiIRC.

Added in 1.9.0

\$ial(nick/mask,[N])

Returns the Nth address matching mask in the Internal Address List.

Parameters

nick/mask - Nick or mask to lookup. (can be a [wildcard](#))

[N] - If N = 0, number of lookup matches, otherwise the Nth match. (optional, default i 1)

Properties

.nick - The user nick.

.user - The user ident.

.host - The user hostname.

.addr - The user ident@hostname.

.mark - The user [mark](#).

.gecos - The user realname/fullname.

.name - The user realname/fullname.

.realname - The user realname/fullname. (AdiIRC only)

.account - The user account name. ([IRCv3](#) feature)

.isaway - Returns [\\$true](#) if the user is away, otherwise [\\$false](#). (**AdiIRC only**)

.away - Returns [\\$true](#) if the user is away, otherwise [\\$false](#).

.id - Returns a unique id for this user.

Example

```
; Print the address 'ident!nick@hostname' for 'nick'.  
//echo -ag $ial(nick)
```

```
; Print the number of matches for wildcard search 'nick*'.  
//echo -ag $ial(nick*, 0)
```

```
; Print the realname for second match using wildcard search 'nick*'.  
//echo -ag $ial(nick*, 2).realname
```