

AdiIRC - \$ignore - # 5

Added in 1.9.0

\$ignore

Returns [\\$true](#) if [/ignore](#) is enabled, otherwise [\\$false](#).

\$ignore(N|address)

Returns the Nth address in the ignore list set in [Options](#) -> [Ignore](#) or using [/ignore](#).

Parameters

N|address - An address or if N = 0, number of addresses, otherwise the Nth address.

Properties

.network - The network associated with the ignore. (if any)
.type - Ignore flags.
.secs - Number of seconds until the ignore expire. (if set to expire)
.note - Returns the note. **(AdiIRC only)**
.channel - Returns channel(s). **(AdiIRC only)**
.text - Returns match text. **(AdiIRC only)**
.cs - Returns [\\$true](#) if case sensitive otherwise [\\$false](#). **(AdiIRC only)**
.regex - Returns [\\$true](#) if regex otherwise [\\$false](#). **(AdiIRC only)**

Examples

```
; Add a ignore for the nick 'Example'  
/ignore -u1000 Example
```

```
; Print number of addresses in the ignore list.  
//echo -ag $ignore(0)
```

```
; Print information about the 'Example' ignore.  
//echo -ag $ignore(Example) type is $ignore(Example).type secs is $ignore(Example).secs
```