

## AdiIRC - Aop - # 4

Added in 3.1

**/aop [-lrw] <on|off|nick|address> [#channel1,#channel2,...] [type] [network]**

Add/remove/list users from the auto-op list.

/aop with no parameters shows [\\$true](#) if auto-op is enabled, otherwise [\\$false](#).

See also [\\$aop](#), [/aop](#), [/avoice](#), [\\$protect](#), [\\$avoice](#).

### Switches

- l - Prints all auto-op users.
- r - Removes a address from the auto-op list. (if no address is specified, clears the auto-op list)
- w - Indicate the auto-op should be enabled on all networks.

### Parameters

- on - Turns auto-op on.
- off - Turns auto-op off.
- address - The address or nick to add/remove from the auto-op list.
- [#channel1,#channel2,...] - List of channels to auto-op in.
- [type] - A number representing a [\\$mask](#) to use. (if user is not found in the internal address list, a lookup is performed)
- [network] - The network to auto-op in.

### Example

```
; Adds 'nick!nick@42.42.42.42' to the auto-op list on the channel '#channel'  
/aop nick!nick@42.42.42.42 #channel
```

```
; Adds 'nick!*@*' to the auto-op on any channel.  
/aop nick
```

```
; Remove 'nick!nick@42.42.42.42' from the auto-op.  
/aop -r nick!nick@42.42.42.42
```