

AdiIRC - Loadbuf - # 8

Added in 1.9.0

/loadbuf [**lines**] [**-acNegilmnoprst**<topic>] <window | dialog id> <filename>

Loads the specified number of lines from the end of the file of filename into the specified window.

- a - Loads the text into the active window.
- cN - Specifies the default color (N) for the line being read.
- e - Evaluates variables and identifiers in the line being read.
- g - **TODO**
- i - **TODO**
- l - Reads the lines into side-listbox in a custom window.
- m - Indicates that the logging text is already timestamped.
- n - Logs the loaded text to a log file, if logging is enabled for that window
- o - Indicates that you have specified the [dialog id] parameters instead of a window name in order to load lines into a custom dialog control.
- p - **TODO**
- r - Clears the contents of the output window before adding read lines.
- s - Reads the lines into the associated status window.
- t<topic> - Loads the text under the [topic] section in an INI or plain text file.

Parameters

[lines] - If specified, the number of lines to add from the end the file, otherwise the whole content of the file is added.

<window | dialog id> - Window or dialog id to load into.

<filename> - File to load.

Example

```
; Open a custom window.
```

```
/window @Example
```

```
; Read 10 lines from the AdiIRC config file into the custom window
```

```
//loadbuf 10 -r @Example $qt($adiircini)
```

```
; Only loads the [Messages] AdiIRC section of the config file.
```

```
//loadbuf -rTMessages @Example $qt($adiircini)
```